

# Heavy Duty Swivel Links/Swivel Joints



Our range of full load swivel links facilitate a flexible rotational connection between the winch bond and the cable thus protecting the cable whilst allowing the bond to naturally rotate. All swivels have a safety factor of 3:1

Code	SWL	Diameter	Length	Jaw Width	Pin Dia.
<u>SW0.35T</u>	350Kg	17.5mm	60mm	10mm	6mm
<u>SW0.75T</u>	750Kg	26mm	84mm	15mm	8mm
<u>SW2.0T HD</u>	2,000Kg	31mm	137mm	14mm	11mm
<u>SW3.0T HD</u>	3,000Kg	32mm	137mm	15mm	12.5mm
<u>SW5.0T HD</u>	5,000Kg	39mm	150mm	17mm	14.5mm
<u>SW7.0T HD</u>	7,000Kg	42mm	185mm	17mm	16mm
<u>SW8.0T HD</u>	8,000Kg	45mm	173mm	20mm	16mm
<u>SW10.0T HD</u>	10,000Kg	52mm	183mm	21mm	17.5mm
<u>SW20.0T HD</u>	20,000Kg	60mm	255mm	26mm	24mm
<u>SW30.0T HD</u>	30,000Kg	80mm	350mm	36mm	30mm

All swivels from 3 tonne upwards are supplied with pin removal tool

## Articulated Swivel

Articulated swivel links assist around bends and when passing through running out/snatch blocks

Code	SWL	Diameter	Length	Jaw Width	Pin Dia.
<u>SW3TA HD</u>	3,000Kg	32mm	130mm	13.5mm	12mm
<u>SW6TA HD</u>	6,000Kg	48mm	185mm	16.5mm	16mm



TWS are proactive in product development and enhancement and as such the specifications are subject to alteration without prior notice

Trailer & Winch Solutions Ltd, Unit 5, Welsh Croft Close, Kirkby in Ashfield, NG17 8EP  
Tel: 01623 752088 – Mob: 07729 967395 – Email: sales@twsltd.co.uk